

AMEETUFF®

info@ameetuff.in

ISO 9001:2015

ISO 14001:2015

ARC 244 SB

HS CODE- 3214 90 90

Ameetuff Fire Stop Barrier Sealant INTRODUCTION

Ameetuff Fire stop barrier sealant is based of silicon polymer compound and it gives flexible, fire-resistant elastomeric finish is primarily used for fire and temperature insulation to prevent the migration of air into the duct air flow and insulation system via duct joints. Is also recommended for sealing duct joint for metal to metal surfaces and it do gives chemical and corrosion protection to the ducting system.



Physical and chemical properties of Fire stop barrier sealant

Colour	Off white/black/grey
Flesh point	Not applicable
Specific gravity	1.29
Solubility	Water soluble
Effect on skin	nil
Water resistance	good
Fire resistance when dry	No spread of fire
Drying time	3 to 4 hour
Complete hard dry	48 hour
Water vapor and air transmission	As per ASTM E 96 less than 0.01 PERM

Chemical resistance	good
Salt water resistance	good
Fire retardant properties	good
Chemical nature	Silicon polymer compound
Application	by spatula
Particle size	less than 5 micron
Temp resistance	up to 800-900°C
Storage life	Nine month



FOR MORE DETAILS: -

WEBSITE
CONTACT NO.
E-MAIL

WWW.AMEETUFF.IN
9811013830
info@ameetuff.in
ameetuff@yahoo.com

DISCLAIMER

The information contained within this page is based on information believed to be reliable at the time of its preparation. The Company will not be liable for loss or damage howsoever caused including liability of negligence which may be suffered by the user of the data contained herein. It is the user's responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of results is implied since conditions of use are beyond our control.

Important Notice to User: The technical information, recommendations and other statements contained in this document are based upon tests or experience that believes are reliable, but the accuracy or completeness of such information is not guaranteed. Product Use: Many factors beyond Ameetuff's control and uniquely within user's knowledge and control can affect the use and performance of a Ameetuff product in a particular application. Given the variety of situations and factors that can affect the use and performance of a Ameetuff product, user is solely responsible for evaluating the Ameetuff product and determining whether it is fit for a particular purpose and suitable for user's method of application. Warranty and Limited Remedy: Ameetuff warrants that each Ameetuff Product will be free from defects in material and manufacture for 30 days from the date of purchase from Ameetuff's or its authorized distributor. Ameetuff MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a Ameetuff product does not conform to this warranty, the sole and exclusive remedy is, at Ameetuff's option, replacement of the Ameetuff product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, Ameetuff will not be liable for any loss or damage arising from the Ameetuff product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory.

***** (Copy right reserved part of full copy of data attract legal action as per law of land) *****

© 2014, All Right reserved. Ameetuff Technical Paints Industries